

Large Capacity Vertical Band Saws

Standard Features

- 230/460/60/3 Electricals
- Magnetic Starter with 110V Control Circuit and Overload Protection
- 5 Hp TEFC Motor, with Brake (full stop from max. speed within 10 seconds)
- Dual Range Transmission
- 1" (25.4mm) Chevron type Blade Guides with Back-Up Roller
- 29" (737mm)W x 27" (686mm)L Heavy Duty Cast Iron Table with two-way tilt (5°L & 45°R)
- 29-1/2" (749mm)W x 27-.1/2" (699mm)L Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top (Hydraulic table only) Table Travel 13" (330mm)
- Auxiliary Table 19" (483mm)W x 26-3/4" (679mm)L
- Bonded Rubber Band Wheels
- 110V Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 1" (25.4mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) Year Limited Warranty

Optional Equipment

- 1" (25.4mm) Capacity Blade Welder, Shear and Flash Grinder (Carbon stock only)
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- Chevron Guide Inserts: 1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 1" and 1-1/4"



Specifications	V4014F	V4014H
Throat	40" (1016mm)	40" (1016mm)
Table Height	54" (1372mm)	54" (1372mm)
Work Height (under guide)	14" (356mm)	14" (356mm)
Drive Motor	5 Hp (3.75kw)	5 Hp (3.75kw)
Blade Length	260-263" (6604-6680mm)	
Blade Width	1/8" - 1-1/4" (3.2-31.8mm)	
Blade Speed	50-5200 fpm (15.2-1585mpm)	
Dimensions		
Length	72" (1829mm)	72" (1829mm)
Width	39" (991mm)	41" (1041mm)
Height	113" (1870mm)	113" (1870mm)
Net Weight	2,976lbs (1350kg)	3,395lbs (1540kg)
Shipping Weight	3,395lbs (1540kg)	3,627lbs (1645kg)